

LAY- FLAT PVC HOSE REINFORCED FOR LARGE DIAMETERS



CHARACTERISTICS

Composition: Lay- flat reinforced PVC hose.

Characteristics: Maximum resistance to the elements.

Service Temperature: >From 0 °C to +60 °C

Standard Length: 50 m and 100 m

Diameters of greater than 204 mm (8") manufactured to order

Identification: Smooth internal and external surface. Blue colour and marked ACUAFLEX HD PLUS



Code	Nominal diameter		Service/Bursting Pressure bar	Roll length m.	Maximum flow rate liters / hour
	mm.	Inches			
01450	20	-	7/ 21	100	2.200
01451	25	1	7/ 21	100	3.800
01452	30	-	7/ 21	100	5.400
01453	32	1 1/4	7/ 21	100	6.200
01454	35	-	7/ 21	100	7.000
01455	38	1 1/2	7/ 21	100	8.000
01456	40	-	7/ 21	100	9.000
01457	45	-	7/ 21	100	12.000
01458	51	2	7/ 21	100	16.000
01459	55	-	6/ 18	100	19.000
01460	60	-	6/ 18	100	22.000
01471	63	-	6/ 18	100	24.000
01461	65	2 1/2	6/ 18	100	25.000
01462	70	-	6/ 18	100	30.000
01463	77	3	6/ 18	100	38.000
01464	80	-	6/ 18	100	40.000
01465	90	3 1/2	5/15	100	50.000
01466	103	4	5/15	50 Y 100	62.000
01467	110	-	4/ 14	50	76.000
01468	127	5	4/ 14	50	100.000
01469	152	6	4/ 14	50	150.000
01470	204	8	3/ 10	50	250.000
*01480	257	10	1,5/ 6	30 Y 50	330.000
*01481	308	12	1,5/ 5	30 Y 50	480.000
*01482	359	14	1/ 4,5	30 Y 50	consult
*01483	410	16	1/ 4	20, 30 Y 50	consult

* To order