

OROFLEX



APLICACIONES

- Delivery of water in self-propelled machines for irrigation (Tractor drag)
- Delivery of liquid fertilisers (sludge type)
- Irrigation guns
- Installations in high abrasion conditions
- Front and side pivots

CHARACTERISTICS

**Colour:** Black.

**Composition:** Synthetic rubber and Polyester-Polyamide textile.

**Surface:** Fine ribbed.

**Service Temperature:** >From -20 °C to + 80 °C

**Lengths Available:** Up to 200 m.



Code	Nominal diameter		Wall thickne mm.	Weight/ metre gr.	Service/Bursting Pressure bar	Traction limit for no tearing Kg	Curvature radius mts
	mm.	Inches					
*01310	65	2 1/2	4,5	850	15 / 45	3.100	1,200
*01311	76	3	4,5	1.100	15 / 45	4.700	1,400
01312	90	3 1/2	4,5	1.300	15 / 45	5.300	1,500
01313	102	4	4,5	1.500	10 / 30	7.000	1,500
01314	115	4 1/2	4,5	1.600	10 / 30	10.200	1,700
01315	127	5	4,5	1.850	10 / 30	12.500	1,700
01316	152	6	4,5	2.100	10 / 30	17.600	1,900

\* To order