

## BRAITEL PLP

**Applications:**

Low pressure painting equipment (30 bar) with very aggressive solvents (MEK type), tube and cover with polyurethane permitting external cleaning of the hose.

**Material:**

Internal polyamide tube, polyester textile reinforcement with conducting wires. (conducting).  
Polyurethane cover permitting external cleaning of the hose.

**Surface:** Smooth.

**Identification:**

Marked Braitel PLP

**Colour:** Blue

**Standard length:**

100 metre rolls.

**Temperature Range:**

-40°C. to 100°C.

**Presentation:**

Single or double (TWIN) hose

**Standard:**

ISO 1307.

**APPLICATION:**

Low pressure painting equipment (30 bar) for industrial booths.  
Other diameters and twin hoses manufactured to order.

**TECHNICAL DATA**

Code	Internal-External Diameter (mm)	Service Pressure (bar)	Bursting Pressure (bar)	Estandar Length (Mts.)
02325	6,3 x 10	30	90	100
02326	8 x 13	30	90	100
02327	10 x 15	30	90	100

**TECHNICAL DATA**

Code	Internal-External Diameter (mm)	Weight (g/m)	Roll Weight (kg)	Roll Dimensions (cm)
02325	6,3 x 10	70	7	65x65x20
02326	8 x 13	100	10	70x70x20
02327	10 x 15	130	13	75x75x20

Other diameters or double hose are manufactured to order