

RYLKHOR 10



**Applications:**

Delivery of air and water at low pressure (10 bar).  
 Equipment for cooling using cold industrial water.  
 Cleaning of floors with water and industrial detergents.

**Material:**

Tubing with textile reinforcement continuously manufactured from thermorubber, resistant to the elements and abrasion.

**Surface:**

Ribbed

**Identification:**

Marked Rylkhor 10.

**Standard length:**

100 m up to 12 mm in diameter.  
 50 m from 15 mm upwards.

**Temperature Range:**

-15°C to 60°C.

**Standard:**

ISO 1307.

**APPLICATION:**

Industrial cooling systems using cold water.

**TECHNICAL DATA**

Code	Internal-External Diameter (mm)	Service Pressure (bar)	Bursting Pressure (bar)	Standard Length (m)
02025	8 x 15	20	60	100
02026	10 x 17	20	60	100
02027	12 x 19	15	45	100
02028	15 x 22	15	45	50
02029	18 x 26	10	30	50
02030	19 x 27	10	30	50
02031	22 x 31	10	30	50
02032	25 x 34	10	30	50
02033	30 x 41	10	30	50
02034	35 x 47	10	30	50

**TECHNICAL DATA**

Code	Internal-External Diameter (mm)	Weight (g/m)	Roll Weight (kg)	Dimensions
02025	8 x 15	180	18,0	45x45x20
02026	10 x 17	185	18,5	55x55x20
02027	12 x 19	220	22,0	58x58x20
02028	15 x 22	280	14,0	60x60x20
02029	18 x 26	350	17,5	70x70x20
02030	19 x 27	410	20,5	72x72x20
02031	22 x 31	450	22,5	75x75x20
02032	25 x 34	520	26,0	80x80x20
02033	30 x 41	580	29,0	90x90x20
02034	35 x 47	650	32,5	100x100x25