

RYLKHOR RUBBER



Applications:

Delivery of air and water up to 20 bar pressure.
Cleaning of streets and industrial flooring.
Pneumatic air equipment for vehicles.
Cleaning with hot water.

Material:

Tubing with textile reinforcement continuously manufactured from rubber resistant to the elements and abrasion.

Surface: Ribbed

Identification:

Marked Rylkhor CAUCHO

Standard length:

100 m up to 12 mm in diameter.
50 m from 15 mm upwards.

Temperature Range:

-15°C to +80°C.

Packaging:

Blue coloured polyethylene tape.

Standard: ISO 1307.

APPLICATION:

Cleaning of paving and industrial flooring with hot and cold water.

TECHNICAL DATA

Code	Internal-External Diameter (mm)	Service Pressure (bar)	Bursting Pressure (bar)	Standard Length (m)
02184	8 x 16	20	60	100
02185	10 x 18	20	60	100
02186	12 x 20	12	36	100
02187	15 x 25	12	36	50
02188	19,5 x 29,5	12	36	50
02189	25x36	10	30	50

TECHNICAL DATA

Code	Internal-External Diameter (mm)	Weight (g/m)	Roll Weight (kg)	Roll Dimensions (cm)
02184	8 x 16	200	20	45x45x20
02185	10 x 18	250	25	50x50x20
02186	12 x 20	350	35	55x55x20
02187	15 x 25	400	20	50x50x20
02188	19,5 x 29,5	500	25	55x55x20
02189	25x36	760	38	60x60x25