

RYLPRESS 20



Applications:

Air compressors of up to 20 bar, hydraulic returns, carrying of oils and is also appropriate for phytosanitary products, solvents, etc.

Material:

Blue internal tubing based on thermopolymers, reinforced with polyester fabric and covered with ribbed thermorubber.

Identification:

Marked Rylpress 20

Standard length:

100 m rolls up to 12 mm in diameter.
50 m rolls from 15 mm upwards.

Temperature Range:

-20°C to +60°C.

APPLICATION:

Return line from a hydraulic piston.

TECHNICAL DATA

Code	Internal-External Diameter (mm)	Service Pressure (bar)	Bursting Pressure (bar)	Standard Length (m)
02250	6 x 13	20	60	100
02251	8 x 16	20	60	100
02252	10 x 18	20	60	100
02253	12 x 21	20	60	100
02254	15 x 25	20	60	50
02255	19 x 30	20	60	50
02256	25 x 35	20	60	50

TECHNICAL DATA

Code	Internal-External Diameter (mm)	Weight (g/m)	Roll Weight (kg)	Roll Dimensions (cm)
02250	6 x 13	160	16	40x40x20
02251	8 x 16	190	19	45x45x20
02252	10 x 18	230	23	55x55x20
02253	12 x 21	300	30	58x58x20
02254	15 x 25	370	18,5	60x60x20
02255	19 x 30	580	29	70x70x20
02256	25 x 35	750	37,5	80x80x20