

**HEAVY DUTY CONSTANT FLOW PROFESSIONAL NOZZLE**

- Constant flow rate with all effects (jet-mist).
- Manufactured in light and strong E-LITE material.
- Double rubber protector for protection and handling.
- Ideal for working with foam injectors. The complementary CEP foam expander may be fitted.
- Cleaning system without the need to cut the water flow.
- Valve with anti-shock polymeric lever, available in 6 colours.
- New 2-piece rubber protector for maximum protection and easy handling.

**VIPER CG -1550 115 lpm**

**NOZZLE:**

1" BSP Swivel  
Weight: 1.570 g.  
Length: 23,5 cm.

**TIP:**

1-1/2" BSP Swivel  
Weight: 890 g.  
Length: 18 cm



**VIPER CG-2510 360 lpm**

**NOZZLE:**

1-1/2" BSP Swivel  
Weight: 2.020 g.  
Length: 25 cm.

**TIP:**

1-1/2" BSP Swivel  
Weight: 1.335 g.  
Length: 18 cm.  
360 lpm



**VIPER CG-5016 475 lpm**

**NOZZLE:**

1-1/2" BSP Swivel  
Weight: 2.020 g.  
Length: 25 cm.

**TIP:**

1-1/2" BSP Swivel  
Weight: 1.335 g.  
Length: 18 cm.



**VIPER CG-8020 /1-1/2" 800 lpm**

**NOZZLE:**

1-1/2" BSP Swivel  
Weight: 2.920 g.  
Length: 28,5 cm.

**TIP:**

1-1/2" BSP Swivel  
Weight: 1.660 g.  
Length: 22,5 cm.



**VIPER CG-8020 /2-1/2" 800 lpm**

**NOZZLE:**

2-1/2" BSP Swivel  
Weight: 3.270 g.  
Length: 33 cm.

**TIP:**

1-1/2" BSP Swivel  
Weight: 1.660 g.  
Length: 22,5 cm.



**FLOW RATE TABLE**

Model	Nozzel Pressure		Nozzle Flow Rate		Effect	Effective Reach	
	psi	bar	gpm	lpm		feet	metres
CG - 1550	75	5	26	100	SS	72	22
	100	7	30	115	SS	85	26
	150	10	37	141	SS	98	30
CG - 2510	75	5	82	312	SS	125	38
	100	7	95	360	SS	135	41
	150	10	116	441	SS	144	44
CG - 5016	75	5	108	411	SS	131	40
	100	7	125	475	SS	144	44
	150	10	153	582	SS	154	47
CG - 8020	75	5	182	693	SS	144	44
	100	7	210	800	SS	157	48
	150	10	257	980	SS	164	50