

AUTOMATIC NOZZLE WITH CONSTANT PRESSURE SYSTEMS

- Constant flow rate with all effects (jet-mist).
- BIMATIC system maintains constant working pressure.
- Manufactured in light and strong E-LITE material.
- Range of flow rates from 50 to 800 lpm in 4 models of nozzle
- Cleaning system without the need to cut the water flow.
- Valve with anti-shock polymeric lever, available in 6 colours.
- New 2-piece rubber protector for maximum protection and easy handling.

VIPER FT-1550 60-200 lpm

NOZZLE:
1" BSP Swivel/fixed
Weight: 1.610 g.
Length: 23.5 cm

TIP:
1-1/2" BSP Swivel
Weight: 930 g.
Length: 18 cm.



VIPER FT-2510. 100-400 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 2.060 g.
Length: 25 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1.375 g.
Length: 18 cm.



VIPER FT-5016 200-600 lpm

NOZZLE
1-1/2" BSP Swivel
Weight: 2.060 g.
Length: 25 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1.375 g.
Length: 18 cm.

VIPER FT-8020 /1-1/2" 300-800 lpm



NOZZLE
1-1/2" BSP Swivel
Peso: 2,960 g
Length: 28,5 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1.700 g.
Length: 22,5 cm.



VIPER FT-8020 /2-1/2" 300- 800 lpm

NOZZLE:
2-1/2" BSP Swivel
Weight: 3.310 g.
Length: 33 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1.700 g.
Length: 22,5 cm.



FLOW RATE TABLE

Model	Nozzel Pressure		Nozzle Flow Rate		Effect	Effective Reach	
	psi	bar	gpm	lpm		feet	metres
FT - 1550	75	5	15	60	SS	69	21
	100	7	23	90	SS	82	25
	150	10	50	200	SS	112	34
FT - 2510	75	5	25	100	SS	121	37
	100	7	38	150	SS	131	40
	150	10	100	400	SS	141	43
FT - 5016	75	5	50	200	SS	128	39
	100	7	70	275	SS	138	42
	150	10	160	600	SS	151	46
FT - 8020	75	5	80	300	SS	131	40
	100	7	145	550	SS	144	44
	150	10	200	800	SS	161	49