

HIGH PERFORMANCE FIRE FIGHTING NOZZLE WITH FLOW RATE SELECTION

- Constant flow rate with all effects and at all flow rates.
- Ring for manual selection between 4 flow rates, without changing the effect.
- Manufactured in light and strong E-LITE material.
- Designed for working with foam injectors. The complementary CEP foam expander may be fitted.
- Cleaning system without changing the effect or needing to cut the water flow.
- Valve with anti-shock polymeric lever, available in 6 colours.

VIPER SG-1560. 50-125-200-230 lpm

NOZZLE:
1" BSP Swivel
Weight: 1,560 g
Length: 20 cm.

TIP:
1-1/2" BSP Swivel
Weight: 880 g.
Length: 15 cm.



VIPER SG-3012 115-230-360-475 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 1.940 g.
Length: 22,5 cm

TIP:
1-1/2" BSP Swivel
Weight: 1.255 g.
Length: 15,5 cm.



NOTE:
The weights and dimensions of the nozzle include the necessary accessories for the fitting of "break away" nozzle

VIPER SG-7515 265 - 380 - 500 - 600 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 1.940 g.
Length: 22,5 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1.255 g.
Length: 15,5 cm.

VIPER SG-9520/1-1/2" 350 - 500 - 600 - 800 lpm

NOZZLE:
1-1/2" BSP Swivel
Weight: 2.980 g.
Length: 28,5 cm

TIP:
1-1/2" BSP Swivel
Weight: 1.720 g.
Length: 22 cm.



VIPER SELECT



VIPER SG-12250 / 2-1/2" 500 - 600 - 800 - 1000 lpm

NOZZLE:
2-1/2" BSP Swivel
Weight: 3.330 g.
Length: 32,5 cm.

TIP:
1-1/2" BSP Swivel
Weight: 1.720 g.
Length: 22 cm.



VIPER SG nozzle are available in 3 flow rate versions + shut-off in the nozzle for the fitting of "break away" nozzle.

FLOW RATE TABLE

Model	Nozzel Pressure		Nozzle Flow Rate		Effect	Effective Reach	
	psi	bar	gpm	lpm		feet	metres
SG - 1560	75	5	13	43	Chorro	59	18
			26	108	Chorro	82	25
			43	173	Chorro	92	28
			52	199	Chorro	102	31
	100	7	15	50	Chorro	62	19
			30	125	Chorro	85	26
			50	200	Chorro	98	30
			60	230	Chorro	108	33
	125	8,5	17	56	Chorro	69	21
			34	140	Chorro	98	30
			56	224	Chorro	105	32
			67	257	Chorro	108	33
SG - 3012	75	5	26	100	Chorro	75	23
			52	199	Chorro	105	32
			82	312	Chorro	125	38
			108	411	Chorro	131	40
	100	7	30	115	Chorro	85	26
			60	230	Chorro	112	34
			95	360	Chorro	131	40
			125	475	Chorro	141	43
	125	8,5	34	129	Chorro	92	28
			67	257	Chorro	118	36
			106	402	Chorro	138	42
			140	531	Chorro	148	45
SG - 7515	75	5	65	229	Chorro	112	34
			87	329	Chorro	121	37
			108	433	Chorro	135	41
			130	520	Chorro	138	42
	100	7	75	265	Chorro	118	36
			100	380	Chorro	138	42
			125	500	Chorro	144	44
			150	600	Chorro	148	45
	125	8,5	84	296	Chorro	125	38
			112	425	Chorro	141	43
			140	559	Chorro	151	46
			168	671	Chorro	157	48
SG-9520	75	5	82	303	Chorro	121	37
			108	433	Chorro	131	40
			130	520	Chorro	141	43
			173	693	Chorro	144	44
	100	7	95	350	Chorro	128	39
			125	500	Chorro	141	43
			150	600	Chorro	148	45
			200	800	Chorro	154	47
	125	8,5	106	391	Chorro	128	39
			140	559	Chorro	141	43
			168	671	Chorro	144	44
			224	894	Chorro	161	49
SG - 12250	75	5	94	375	SS	125	38
			113	450	SS	135	41
			150	600	SS	144	44
			188	750	SS	148	45
	100	7	125	500	SS	131	40
			150	600	SS	144	44
			200	800	SS	151	46
			250	1000	SS	157	48
	125	8,5	140	559	SS	135	41
			168	671	SS	144	44
			224	894	SS	154	47
			280	1118	SS	164	50